



DAE

3

540
(rpm)

STRENX™ PERFORMANCE STEEL
HARDOX® IN MY BODY

Specially designed for clearing and maintaining fields and plantations.

Idéales pour le nettoyage et l'entretien des plantations et des cultures.

Mowers designed for medium power tractors.

- Chassis made with high - strength steel.
- Rotor with 16 mm Grade 80 chains.
- Hardox blades (optional).
- Category II hitch.
- Front and rear protection chains.
- Height-adjustable skids.
- Rear wheel (option).
- Gearbox 1"3/8 at 540 rpm.
- Reinforced shaft transmission.
- Meets relevant safety standards.
- CE certification.

Gyrobroyeur pour tracteur de moyenne puissance.

- Structure en acier suédois à haute limite d'élasticité.
- Rotor équipé avec chaînes 16 mm grade 80.
- Hardox lames (opcion).
- Attelage CAT II.
- Protections avant et arrière avec chaînes.
- Patins réglables en hauteur.
- Roue arrière (opcion).
- Groupe 1"3/8 et régime 540 rpm.
- Cardan renforcé.
- Autocollants de sécurité.
- Certification CE.

Technical specifications / Caractéristiques techniques

CODE	WORKING WIDTH - LARGEUR DE TRAVAIL (mm)	WIDTH - LARGEUR (mm)	HEIGHT - HAUTEUR (mm)	LENGTH - LONGUEUR (mm)	CHAINS - CHAINES	POWER - PUISSANCE MIN-MAX (HP-CH)	WEIGHT - POIDS (kg)	RPM - TPM
091468251	1.500	1.600	950	1.750	3	50 - 100	375	460
091468252	1.800	1.900	950	2.050	3	60 - 100	450	550
091468253	2.000	2.100	950	2.250	3	80 - 100	500	620
091468254	2.200	2.300	950	2.450	3	90 - 100	550	690

Optional / Opcion

CODE	DESCRIPTION
091018066	Rear support wheel / Roue de support arrière

MEDIA

WEB