



ODE

3

540
(rpm)

STRENX PERFORMANCE STEEL
HARDOX IN MY BODY

Specially designed for clearing and maintaining fields and plantations.

Idéales pour le nettoyage et l'entretien des plantations et des cultures.

Mowers designed for medium power tractors.

- Chassis made with high - strength steel.
- Rotor with 16 mm Grade 80 chains.
- Hardox blades (optional).
- Category II hitch.
- 500mm hydraulic displacement.
- Front and rear protection chains.
- Height-adjustable skids.
- Rear wheel (option).
- Gearbox 1"3/8 at 540 rpm.
- Reinforced shaft transmission.
- Meets relevant safety standards.
- CE certification.

Gyrobroyeur pour tracteur de moyenne puissance.

- Structure en acier suédois à haute limite d'élasticité.
- Rotor équipé avec chaînes 16 mm grade 80.
- Hardox lames (opcion).
- Attelage CAT II.
- Déplacement hydraulique 500 mm.
- Protections avant et arrière avec chaînes.
- Patins réglables en hauteur.
- Roue arrière (opcion).
- Groupe 1"3/8 et régime 540 rpm.
- Cardan renforcé.
- Autocollants de sécurité.
- Certification CE.

Technical specifications / Caractéristiques techniques

CODE	WORKING WIDTH - LARGEUR DE TRAVAIL (mm)	WIDTH - LARGEUR (mm)	HEIGHT - HAUTEUR (mm)	LENGTH - LONGUEUR (mm)	CHAINS - CHAINES	POWER - PUISSANCE MIN-MAX (HP-CH)	WEIGHT - POIDS (kg)	RPM - TPM
2308060001	1.500	1.600	950	1.750	3	50 - 100	615	540
2308060002	1.800	1.900	950	2.050	3	60 - 100	665	540
2308060003	2.000	2.100	950	2.250	3	80 - 100	765	540
2308060004	2.200	2.300	950	2.450	3	90 - 100	815	540

Optional / Opcion

CODE	DESCRIPTION
091018066	Rear support wheel / Roue de support arrière

MEDIA

WEB