



DFO

4

540
(rpm)

STRENX™ PERFORMANCE STEEL
HARDOX® IN MY BODY

Specially designed for forestry works.

Spécialement conçu pour les travaux forestiers.

Mowers designed for medium and high power tractors.

- Chassis made with high - strength steel.
- Rotors with 20 mm Grade 80 chains.
- Rotor with 2 levels.
- Category II hitch.
- Chassis built in 2 levels.
- Optional: Rear push frame.
- Optional: Hydraulic rear hood.
- Toolbox.
- Front and rear protection chains.
- Height-adjustable skids.
- Gearbox with 1”3/4 at 540 rpm.
- Reinforced shaft transmission.
- Meets relevant safety standards.
- CE certification.

Gyrobroyeur pour tracteur de moyenne et forte puissance.

- Structure en acier suédois à haute limite d’élasticité.
- Rotors équipé avec chaînes 20 mm grade 80.
- Rotor avec 2 niveaux de coupe.
- Attelage CAT II.
- Chassis en double niveau.
- Opcion: Rabatteur de branches mécanique.
- Opcion: Porte arrière hydraulique.
- Caisse à outils intégré.
- Protections avan t et arrière avec chaînes.
- Patins réglables en hauteur.
- Groupe 1”3/4 et régime 540 rpm.
- Cardan renforcé.
- Autocollants de sécurité.
- Certification CE.

Technical specifications / Caractéristiques techniques

CODE	WORKING WIDTH - LARGEUR DE TRAVAIL (mm)	WIDTH - LARGEUR (mm)	HEIGHT - HAUTEUR (mm)	LENGTH - LONGUEUR (mm)	CHAINS - CHAINES	POWER - PUISSANCE MIN-MAX (HP-CH)	WEIGHT - POIDS (kg)	RPM - TPM
091463189	1.500	1.725	1.400	2.300	4	90 - 250	1.100	540
091463190	1.800	2.025	1.400	2.300	4	120 - 250	1.305	540
2308040001	2.000	2.225	1.400	2.300	4	140 - 250	1.410	540

The weight refers to the standard machine (without accessories) / Le poids se réfère à la machine standard (sans accessoires).

Optional / Opcion

CODE	DESCRIPTION
090477911	Low mechanical push frame / Rabatteur de branches mécanique **DFO**
3030070001	Hydraulic rear hood **DFO** / Porte arrière hydraulique **DFO**

MEDIA WEB

Carretera de Córdoba Km 114
130 Guadalcázar
Córdoba **ESPAÑA**

www.lopezgarrido.com