



SUB

Specially designed to remove the hard layer of soil and subsoil, with the aim of ensuring that moisture remains in our land for as long as possible, facilitating rooting and obtaining more fruitful crops.

- Chassis made with high - strenght steel.
- Anti-rotation bolts.
- Integrated support arms.
- Up to 700 mm depth.
- Interchangeable screw-on tips.
- Adjustable working depth.
- 3-point hitch on tractor.
- Protections according to regulations.
- CE certification.

Machine conçue pour éliminer la couche dure du sol et du sous-sol, afin que l'humidité reste le plus longtemps possible dans nos terres, facilitant l'enracinement et obtenant des récoltes plus fructueuses.

- Châssis en Strenx/Hardox
- Boulons anti-rotation intégrés.
- Travailleurs de soutien intégrés.
- Jusqu'à 700 mm de profondeur.
- Embouts à visser interchangeables.
- Profondeur de travail réglable.
- Attelage aux 3 points du tracteur.
- Protections selon la réglementation.
- Certification CE.

Technical specifications / Caractéristiques techniques

CODE	WORKING WIDTH - LARGEUR DE TRAVAIL (mm)	WIDTH - LARGEUR (mm)	HEIGHT - HAUTEUR (mm)	LENGTH - LONGUEUR (mm)	Nº. ARMS - Nbre. BRAS	POWER - PUISSANCE MIN-MAX (HP-CH)	WEIGHT - POIDS (kg)	WORKING DEPTH - PROFONDEUR DE TRAVAIL
091600338	-	980	1.300	1.200	1	70 - 100	210	700
091602537	1.300	1.400	1.300	1.200	3	70 - 120	400	700
091602539	2.000	2.150	1.300	1.200	5	90 - 130	560	700
091602540	2.740	2.900	1.300	1.200	7	120 - 140	750	700

Optional / Opcion

CODE	DESCRIPTION
3620000001	Rear roller Ø 520mm / Rouleau arrière Ø 520mm

MEDIA

WEB

Carretera de Córdoba Km 114
130 Guadalcázar
Córdoba **ESPAÑA**

www.lopezgarrido.com