



TGK

4

540
(rpm)

70
(Ø mm)

STRENX™ PERFORMANCE STEEL
HARDOX® IN MY BODY

Specially designed for working on grass, vineyards, green spaces and pruning waste, with a maximum diameter of 7 cm.

Outil idéal pour le broyage d'herbe, sarments de vigne et restes de tailles d'arbres fruitiers jusqu'à 7 cm de diamètre.

Mulcher designed for medium power tractors.

- Chassis made with high - strength steel.
- Rotor diameter: 460mm.
- 450mm hydraulic shifting.
- Rear levelling roller.
- Category II hitch.
- Rear retaining pins.
- Forged and hardened hammers with 18mm screw.
- 2 rows of bolt-on Hardox counter-blades.
- Side transmission by 4 XPB belts.
- Front protection.
- Height-adjustable skids.
- Gearbox with free-wheel 1"3/8 at 540rpm.
- Reinforced shaft transmission.
- Meets relevant safety standards.
- CE certification.

Broyeur conçu pour les tracteurs de moyenne puissance.

- Chassis construit en acier à haute limite élastique.
- Rotor de 460 mm de diamètre.
- Deplacement hydraulique 450 mm.
- Rouleau arrière.
- Attelage Cat II.
- Dents de rétention.
- Marteaux forgés et endurcies avec boulon de 20mm.
- 2 lignes de contre-couteaux.
- Transsmision latérale par 4 courroies XPB.
- Protection frontale.
- Patins réglables en hauteur.
- Groupe avec roue libre. 540Tr/min.
- Cardan renforcé.
- Protections suivant les normes Euro.
- Certificat CE.

Technical specifications / Caractéristiques techniques

CODE	WORKING WIDTH - LARGEUR DE TRAVAIL (mm)	WIDTH - LARGEUR (mm)	HEIGHT - HAUTEUR (mm)	LENGTH - LONGUEUR (mm)	HAMMERS - MARTEAUX	POWER - PUISSANCE MIN-MAX (HP-CH)	WEIGHT - POIDS (kg)	RPM - TPM
3822060060	1.600	1.800	545	1.380	12	60 - 120	760	540
3822060061	1.800	2.000	545	1.380	16	70 - 120	805	540
3822060062	2.000	2.200	545	1.380	18	80 - 120	850	540
3822060063	2.200	2.400	545	1.380	22	85 - 120	900	540
3822060064	2.400	2.600	545	1.380	22	90 - 120	945	540



HAMMERS
MARTEAUX **TG**

MEDIA

WEB

Carretera de Córdoba Km 114
130 Guadalcázar
Córdoba **ESPAÑA**

www.lopezgarrido.com