



TPY

6

540
(rpm)

200
(Ø mm)

STRENX™ PERFORMANCE STEEL
HARDOX® IN MY BODY

Specially designed for crushing stones, up to a diameter of 20 cm.

Broyeur de pierre jusqu'à 20 cm de diamètre.

Mulcher designed for medium and high power tractors.

- Chassis made with high - strength steel.
- Rotor diameter: 450 mm.
- Category II hitch.
- Hydraulic rear hood.
- Fixed tungsten hammers.
- Bolt-on Hardox 500 counter-blades.
- Sieve on rear hood.
- Leveller for mulched material.
- 4 lines of front protection chains.
- Side transmission by 6 XPB belts.
- Height-adjustable skids.
- Gearbox with free-wheel 1"3/4 at 540 rpm.
- Reinforced shaft transmission.
- Meets relevant safety standards.
- CE certification.

Broyeur pour tracteurs de moyenne et forte puissance.

- Châssis construit en acier à haute limite d'élasticité.
- Rotor de 450 mm de diamètre.
- Atellage Cat II.
- Porte arrière hydraulique.
- Marteaux fixe en Tungstène.
- Contre couteaux démontables en Hardox 500.
- Crible sur la porte arrière.
- Nivelation de la matière broyée.
- 4 lignes de chaines antiprojections.
- Transmission par 6 courroies XPB.
- Patins réglables en hauteur.
- Groupe avec roue libre 1"3/4 et régime d'entrée 540 rpm.
- Cardan renforcé.
- Protections suivant normes.
- Certificcation CE.

Technical specifications / Caractéristiques techniques

CODE	WORKING WIDTH - LARGEUR DE TRAVAIL (mm)	WIDTH - LARGEUR (mm)	HEIGHT - HAUTEUR (mm)	LENGTH - LONGUEUR (mm)	HAMMERS - MARTEAUX	POWER - PUISSANCE MIN-MAX (HP-CH)	WEIGHT - POIDS (kg)	RPM - TPM
3822150001	1.000	1.340	1.435	1.200	24	70 - 140	920	540
3822150002	1.300	1.640	1.435	1.200	30	80 - 140	1.050	540
3822150003	1.600	1.940	1.435	1.200	36	90 - 140	1.175	540
3822150004	1.800	2.140	1.435	1.200	38	100 - 140	1.260	540



HAMMERS
MARTEAUX **TY**

MEDIA

WEB

Carretera de Córdoba Km 114
130 Guadalcázar
Córdoba **ESPAÑA**

www.lopezgarrido.com