



TSV

4

540
(rpm)

80
(Ø mm)

STRENX PERFORMANCE STEEL
HARDOX IN MY BODY

Specially designed for crushing pruning waste from vineyards, fruit trees, olive trees, etc., up to a diameter of 8 cm.

Broyeur spécial pour sarments de vigne, les restes d'élagage d'arbres fruitiers, d'oliviers, etc. Jusqu'à un diamètre de branche de 8 cm.

Mulcher designed for medium power tractors.

- Chassis made with high - strength steel.
- Rotor diameter: 450 mm
- Category II hitch.
- Hydraulic bottom pick-up feeder
- Separate mulching chamber
- Forged and hardened hammers with 18 mm screw.
- 2 rows of Hardox counter-blades.
- Side transmission by 4 XPB belts.
- Pneumatic rear wheels.
- Height-adjustable skids.
- Gearbox with free-wheel 1"3/4 at 540rpm
- Reinforced shaft transmission.
- Meets relevant safety standards.
- CE certification.

Broyeur conçu pour des tracteurs de moyenne puissance.

- Chassis en acier à haute limite élastique.
- Rotor de 450 mm de diamètre.
- Attelage Cat II.
- Pick-up à entrainement hydraulique.
- Chambre de broyage indépendante.
- Marteaux forgés et endurcis avec axe de 18 mm.
- 2 lignes de contre couteaux en Hardox.
- Transmission latérale par 4 courroies XPB.
- Roues arrières pneumatiques réglables.
- Patins réglables en hauteur.
- Boitier avec roue libre 1"3/4 Z6 à 540 rpm.
- Transmission cardan renforcé.
- Protections suivant normes.
- Certificat CE.

Technical specifications / Caractéristiques techniques

CODE	WORKING WIDTH - LARGEUR DE TRAVAIL (mm)	WIDTH - LARGEUR (mm)	HEIGHT - HAUTEUR (mm)	LENGTH - LONGUEUR (mm)	HAMMERS - MARTEAUX	POWER - PUISSANCE MIN-MAX (HP-CH)	WEIGHT - POIDS (kg)	RPM - TPM
38222110001	900	1.150	1.500	1.500	8	50 - 100	780	540
3822050002	1.100	1.350	1.500	1.500	10	55 - 100	849	540
3822050003	1.300	1.550	1.500	1.500	10	60 - 100	920	540
091468246	1.500	1.750	1.500	1.500	12	70 - 100	997	540
091468247	1.800	2.050	1.500	1.500	16	80 - 100	1.077	540
3822050001	2.000	2.250	1.500	1.500	18	80 - 100	1.117	540

Optional / Opcion

CODE	DESCRIPTION
3030030050	Double entry group / Groupe à double entrée
3030030047	Retention sieve 25 mm / Tamis de rétention 25 mm
3030030048	Retention sieve 35 mm / Tamis de rétention35 mm
3030030049	Retention sieve 45 mm / Tamis de rétention 45 mm



HAMMERS
MARTEAUX **TG**

When ordering, please indicate the tractor model and the type of crop to be shredded.
Lors de la commande, indiquez le modèle de tracteur et le type de récolte à broyer.

MEDIA

WEB

Carretera de Córdoba Km 114
130 Guadalcázar
Córdoba **ESPAÑA**

www.lopezgarrido.com