



LÓPEZ GARRIDO

AGRICULTURAL MACHINERY

MULCHERS / BROYEURS
all-purpose / axe horizontal



4



540
(rpm)



70
(Ø mm)

STRENX™
PERFORMANCE STEEL
HARDOX®
IN MY BODY



Specially designed for working on grass, vineyards and green spaces and pruning waste, with a maximum diameter of 7 cm.



Idéal pour le broyage de talus enherbé et l'entretien des parcelles. Broie tous types de végétaux et restes de taille jusqu'à 7 cm de diamètre.

Mulcher designed for medium power tractors.

- Chassis made with high - strength steel.
- Rotor diameter: 430 mm.
- 450 mm hydraulic shifting.
- Rear levelling roller.
- Category II hitch.
- Hydraulic rear hood.
- Forged and hardened hammers with 18 mm screw.
- 2 rows of bolt-on Hardox counter-blades.
- Side transmission by 4 XPB belts.
- Front protection.
- Height-adjustable skids.
- Gearbox with free-wheel 1" 3/8 Z6 at 540 rpm.
- Reinforced shaft transmission.
- Meets relevant safety standards.
- CE certification.

Destroçador projetado para tratores de meia potência.

- Châssis construit en acier suédois à haute limite d'élasticité.
- Rotor 430 mm de diamètre.
- Déplacement hydraulique 450 mm.
- Rouleau de nivellement arrière.
- Attelage CAT II.
- Porte arrière hydraulique.
- Marteaux forgés avec boulons de 18 mm.
- 2 rangées de contre-couteaux.
- Transmission latéral par 4 courroies XPB.
- Protection avant par chaînes.
- Patins réglables en hauteur.
- Groupe avec roue libre 1" 3/8 et régime 540 rpm.
- Cardan renforcé.
- Protection sécurité.
- Certification CE.

Características técnicas / Tabela técnica

								
CODE	WORKING WIDTH - LARGEUR DE TRAVAIL (mm)	WIDTH - LARGEUR (mm)	HEIGHT - HAUTEUR (mm)	LENGTH - LONGUEUR (mm)	HAMMERS - MARTEAUX	POWER - PUISSANCE MIN-MAX (HP-CH)	WEIGHT - POIDS (kg)	RPM - TPM
38224360001	1600	1850	1050	1120	12	60- 120	670	540
38224360002	1800	2050	1050	1120	16	70- 120	720	540
38224360003	2000	2250	1050	1120	18	80- 120	780	540



HAMMERS
MARTEAUX **TG**

MEDIA

